

# 5-Port 10/100Mbps Desktop Switch with 4-Port Passive PoE NC-PUS051D-24V

## Features:

- With 4 PoE ports, transfers data and power on one single cable
- Working with 24V passive PoE compliant PDs, expands home and office network
- Requires no configuration and installation
- External power adapter supply



## Description

NC-PUS051D-24V is an 5 10/100Mbps ports unmanaged switch that requires no configuration and provides 4 PoE (Power over Ethernet) ports. It can automatically detect and supply power with all 24V passive PoE compliant Powered Devices (PDs). In this situation, the electrical power is transmitted along with data in one single cable allowing you to expand your network to where there are no power lines or outlets, where you wish to fix devices such as APs, IP Cameras or IP Phones, etc.

 **Specification**

Hardware	
<b>Interface</b>	5 10/100Mbps RJ45 Ports AUTO Negotiation/AUTO MDI/MDIX
<b>Network Media</b>	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 100BASE-TX: UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
<b>PoE Ports (RJ45)</b>	PoE Ports: Port1- Port4 Power Supply: 120W
<b>PoE Pin definition</b>	4/5 (+), 7/8 (-)
<b>Backbound Bandwidth</b>	1Gbps
<b>Power Supply</b>	DC 24V/3A
<b>Fan Quantity</b>	Fanless
<b>Dimensions (L xW x H )</b>	138mm*86mm*25mm

SOFTWARE	
<b>Transfer Method</b>	Store and Forward
<b>MAC Address Table</b>	2K
<b>Advanced Functions</b>	Compatible With 24V passive PoE Compliant PDs Priority Function Mac Address Auto-Learning And Auto-Aging IEEE802.3x Flow Control For Full-Duplex Mode And Backpressure For Half-Duplex Mode

Others	
<b>Certification</b>	CE
<b>Environment</b>	Operating Temperature: 0°C~40°C (32°F~104°F); Storage Temperature: -40°C~70°C (-40°F~158°F); Operating Humidity: 10%~90% non-condensing; Storage Humidity: 5%~90% non-condensing
<b>Package</b>	5-Port 10/100Mbps Desktop Switch with 4-Port PoE Power Adapter User Guide
<b>System Requirements</b>	Microsoft® Windows 8, Windows 7,98SE, NT, 2000, XP, Vista™ , MAC® OS, NetWare®, UNIX® or Linux.

**Diagram**

