

8-Port 100Mbps+ 2-Combo Port

Switch with 8-Port PoE

NC-PUS010GF

Features:

- With 8 PoE ports, transfers data and power on one single cable
- 2 *1000M combo(RJ45+SFP) Uplink port
- Working with IEEE 802.3af/at compliant PDs, expands SMB and office network
- Power Supply: 144W



Description

NC-PUS010GF, 8FE+2SFP+2GE PoE Switch is right for remote 100M wireless cabling and HD monitoring network. Besides with access of high performance, it provides 8 10/100M Base-T Ethernet ports and 2 extra independent 1000Base-X Gigabit SFP and Ethernet port. Ports 1~8 support IEEE 802.3af/at PoE (15.4W/30W) standard; supply electricity and transmit data at the same time to AP, IP Camera or IP Phone via Cat.5 twisted-pair cables. In addition to these, it provides stronger safety protection system. To sum up, 8FE+2SFP+2GE PoE Switch is an ideal and safe switch for easy use.

Specification

Hardware	
Interface	8 10/100Mbps RJ45 Ports 2*10/100/1000Mbps RJ45/SFU Ports AUTO Negotiation/AUTO MDI/MDIX
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 100BASE-TX: UTP category 5, 5e cable (maximum 100m) 1000BASE-TX: UTP category 5e,6 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
PoE Ports (RJ45)	Standard: 802.3af/at compliant PoE Ports: Port1- Port8 Power Supply:144W
Backbound Bandwidth	5.6Gbps
Power Supply	100-240VAC, 50/60Hz
Dimensions (L xW x H)	230mm*170mm*44mm

SOFTWARE	
Transfer Method	Store and Forward
MAC Address Table	8K
Advanced Functions	Compatible With IEEE 802.3af/at Compliant PDs Priority Function Mac Address Auto-Learning And Auto-Aging IEEE802.3x Flow Control For Full-Duplex Mode And Backpressure For Half-Duplex Mode

Others

Environment	Operating Temperature: 0°C~60°C (32°F~140°F); Storage Temperature: -40°C~70°C (-40°F~158°F); Operating Humidity: 10%~90% non-condensing; Storage Humidity: 5%~90% non-condensing
Package	8-Port 100Mbps+ 2-Combo Port Switch with 8-Port PoE 48V/3A Power Adapter User Guide
System Requirements	Microsoft® Windows 8, Windows 7,98SE, NT, 2000, XP, Vista™, MAC® OS, N48VetWare®, UNIX® or Linux.