

5-Port Gigabit Desktop Switch with 4-Port PoE NC-PUS051G

Features:

- 5-Port 10/100/1000Mbps Desktop Switch with 4-Port PoE
- Working with IEEE 802.3af/at compliant PDs, expands home and office network
- Power Supply: 72W
- Steel housing, desktop or wall-mounting design



Description

NC-PUS051G is an 5 10/100/1000Mbps ports unmanaged switch that requires no configuration and provides 4 PoE (Power over Ethernet) ports. It can automatically detect and supply power with all IEEE 802.3af/at compliant Powered Devices (PDs). In this situation, the electrical power is transmitted along with data in one single cable allowing you to expand your network to where there are no power lines or outlets, where you wish to fix devices such as APs, IP Cameras or IP Phones, etc.

 **Specification**

Hardware	
Interface	5 10/100/1000Mbps RJ45 Ports AUTO Negotiation/AUTO MDI/MDIX
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) 100BASE-TX: UTP category 5, 5e cable (maximum 100m) 1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
PoE Ports (RJ45)	Standard: 802.3 af /802.3at compliant PoE Ports: Port1- Port4 Power Supply: 72W
Backbound Bandwidth	10Gbps
Power Supply	DC 48V/1.5A
Fan Quantity	Fanless
Dimensions (L xW x H)	151mm*126mm*36mm

SOFTWARE	
Transfer Method	Store and Forward
MAC Address Table	8K
Advanced Functions	Compatible With IEEE 802.3af/802.3at Compliant PDs Priority Function Mac Address Auto-Learning And Auto-Aging IEEE802.3x Flow Control For Full-Duplex Mode And Backpressure For Half-Duplex Mode

Others

Certification	FCC, CE
Environment	Operating Temperature: 0°C~40°C (32°F~104°F); Storage Temperature: -40°C~70°C (-40°F~158°F); Operating Humidity: 10%~90% non-condensing; Storage Humidity: 5%~90% non-condensing
Package	5-Port Gigabit Desktop Switch with 4-Port PoE Power Adapter
System Requirements	Microsoft® Windows 8, Windows 7, 98SE, NT, 2000, XP, Vista™, MAC® OS, NetWare®, UNIX® or Linux.