

24-Port 1000Mbps Rackmount Switch with 24-Port PoE

NC-PUS324G

Features:

- With 24*1000Mbps PoE ports, transfers data and power on one single cable
- Working with IEEE 802.3af/802.3at compliant PDs, expands home and office network
- Power Supply: 400W
- 19 Inch rack-mountable steel case



Description

NC-PUS324G 24-Port 10/100/1000Mbps Rackmount Switch with 24-Port PoE provides the seamless network connection. It integrates 1000Mbps Giga Ethernet and 100Mbps Fast Ethernet network capabilities. 24 Auto-Negotiation RJ45 ports of the switch support Power over Ethernet (PoE) function. These PoE ports can automatically detect and supply power with those IEEE 802.3af/at compliant Powered Devices (PDs). In this situation, the electrical power is transmitted along with data in one single cable allowing you to expand your network where there are no power lines or outlets, where you wish to fix devices such as APs, IP Cameras or IP Phones, etc.

 **Specification**

Hardware	
Interface	24*10/100/1000Mbps RJ45 Ports AUTO Negotiation/AUTO MDI/MDIX
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 100BASE-TX: UTP category 5, 5e cable (maximum 100m) 1000BASE-TX: UTP category 5e,6 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
PoE Ports (RJ45)	Standard: 802.3af/at compliant PoE Ports: Port1- Port24 Power Supply: 400W
Backbound Bandwidth	48Gbps
Power Supply	100-240VAC, 50/60Hz
Dimensions (L xW x H)	430mm*240mm*45mm

SOFTWARE	
Transfer Method	Store and Forward
MAC Address Table	16K
Advanced Functions	Compatible With IEEE 802.3af/at Compliant PDs Priority Function Mac Address Auto-Learning And Auto-Aging IEEE802.3x Flow Control For Full-Duplex Mode And Backpressure For Half-Duplex Mode

Others

Environment	Operating Temperature: 0°C~40°C (32°F~104°F); Storage Temperature: -40°C~70°C (-40°F~158°F); Operating Humidity: 10%~90% non-condensing; Storage Humidity: 5%~90% non-condensing
Package	24-Port 1000Mbps Rackmount Switch with 24-Port PoE Power Adapter
System Requirements	Microsoft® Windows 8, Windows 7, 98SE, NT, 2000, XP, Vista™, MAC® OS, NetWare®, UNIX® or Linux.