

2.4GHz 300Mbps Outdoor CPE

NC-AP211M



Features:

- Wireless N high speed (up to 300Mbps)
- Plug and play, no need config
- Support Power Over Ethernet
- Internal 8dBi directional antenna, up to 1KM+
- Multi-wireless modes to expand the wireless network: AP, Repeater
- Support LED display and 802.1Q VLAN Tagging
- Outdoor weatherproof and 4000V lightning/15KV ESD protection design

www.nc-link.cn



Description

NC-AP211M is High Performance Wireless outdoor CPE, and it is dedicated to long distance wireless network solutions, which is a revolutionary design with its features of conciseness, quality, and flexibility. It features 11dBi internal directional Antenna and high RX sensitivity can significantly extend the transmission range up to 1km to deliver a more stable wireless connection and reduce the expense of equipment.

NC-AP211M provides multiple - operation modes for users to buildup network or access internet : AP, Repeater. Featuring passive power over Ethernet function is easy to deploy.

No need config, just plug and play! It can help you to build your wireless network in a snap.

Specification

Wireless	
Standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Signal Rate	Up to 300Mbps
Chipset	MTK 580MHz
Frequency Range	2.4GHz-2.484GHz
Transmit Power	20dBm(MAX)
Data Transfer Rates	802.11n: 40MHz(150Mbps, 135Mbps, 120Mbps, 90Mbps, 60Mbps, 45Mbps, 30Mbps, 15Mbps) 20MHz (72Mbps, 65Mbps, 57Mbps, 43Mbps, 28Mbps, 21Mbps, 14Mbps, 7Mbps) 801.11g: (54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 11Mbps, 9Mbps, 6Mbps) 802.11b: (11Mbps,9Mbps, 6Mbps, 5.5Mbps, 2Mbps, 1Mbps)
Wireless Modes	AP, Repeater
Wireless Security	64/128-bit WEP, WPA-PSK/WPA2-PSK (TKIP/AES) SSID Broadcast Enable/Disable Wireless MAC Filtering

www.nc-link.cn



Hardware	
Standards	IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX
Interfaces	1 * 10/100M Auto MDI/MDIX RJ45 LAN port
LED Indicators	PWR, Wi-Fi, LAN, WAN
Buttons	Mode button, Fn,S, Reset
Antenna	Build –in 8dBi Antenna
Power Supply	24V/0.5A Passive PoE
Power Consumption	≤ 5W
Dimensions (L x W x H)	168*88*57.6mm
Weight	235g

Software	
Wi-Fi	Multiple SSID, Wi-Fi Timer Off, WLAN Partition, Short GI, Coverage Threshold and TX Power control
Access Control	MAC ALC
VPN Pass-through	PPTP, L2TP, IPSEC
Others	VLAN Tagging, Firmware upgrade, Watch dog, Wi-Fi Analyzer

Others	
Environment	Operating Temperature: 0°C~40°C
	Storage Temperature: -40 $^{\circ}$ C $^{\sim}$ 70 $^{\circ}$ C
	Operating Humidity: 10%~90% non-condensing
	Storage Humidity: 5%~90% non-condensing
Package	2 * NC-AP211M
	2 * Power Adapter
	2 * Cable Tie
	1 * Quick Installation Guide



Applications



PTP/PTMP Wireless Transmission



Elevator Monitoring Wireless Transmission



Enterprise WLAN interconnection



Long Distance Wireless Connection